


**HELIFLEX IS 866**  
**Heavy Duty**


Abrasion and crush resistant.



Internal Diameter (mm)	25	32	40	50	64	75	100	125	150	200	250
Outside Diameter (mm)	32	41	49	60	76	87	116	140	170	229	279
Mass per metre (g)	0,40	0,68	0,94	1,11	1,68	2,00	3,37	5,20	6,83	12,51	15,58
Bending Radius (mm)	80	120	170	250	350	400	500	1 000	1 500	2 000	2 500
% Vacuum	99	99	99	99	99	99	99	95	95	90	85

**HELIFLEX IS 867**  
**Fuel Resistant**


Good resistance to fuels and gases - refer to PVC chemical resistance chart.



Internal Diameter (mm)	25	32	40	50	64	75	100
Outside Diameter (mm)	32	41	49	60	76	87	113
Mass per metre (g)	0,41	0,72	0,86	1,18	1,78	2,08	3,25
Bending Radius (mm)	80	120	170	250	350	400	500
% Vacuum	99	99	99	99	99	99	99

**HELIFLEX IS 868**  
**NON-TOXIC**

Specially formulated for the conveyance of food products.



Internal Diameter (mm)	25	32	40	50	64	75	100	125	150	200
Outside Diameter (mm)	32	41	49	60	76	87	115	140	170	221
Mass per metre (g)	0,41	0,70	0,85	1,14	1,75	2,05	3,19	5,18	7,31	8,63
Bending Radius (mm)	80	120	170	250	350	400	500	1 000	1 500	2 000
% Vacuum	99	99	99	99	99	99	99	95	95	90

**HELIFLEX IU 756**  
**MEDIUM DUTY URETHANE LINED**

- Highly abrasion resistant.
- Flexible.

Nominal Dimensions (mm)		75	100	130
Internal Diameter		85	115	147
Outside Diameter		1,73	3,77	5,19
Mass (kg/m)		600	800	1 500
Bending Radius (mm)		99	99	95
% Vacuum				

